



# **Universal Enterprise Controller**

## Reference Guide

Universal Products

Version 3.2.0



---

# **Universal Enterprise Controller**

## **Reference Guide Universal Products 3.2.0**

---

<b>Document Name</b>	Universal Enterprise Controller 3.2.0 Reference Guide				
<b>Document ID</b>	uec-ref-3203				
<b>Products</b>	<b>z/OS</b>	<b>UNIX</b>	<b>Windows</b>	<b>OS/400</b>	<b>HP NonStop</b>
Universal Enterprise Controller	✓		✓		
UECLoad	✓		✓		

---

# Stonebranch Documentation Policy

---

This document contains proprietary information that is protected by copyright. All rights reserved. No part of this publication may be reproduced, transmitted or translated in any form or language or by any means, electronic or mechanical, including photocopy, recording, or any information storage and retrieval system, without permission, in writing, from the publisher. Requests for permission to make copies of any part of this publication should be mailed to:

Stonebranch, Inc.  
950 North Point Parkway, Suite 200  
Alpharetta, GA 30005 USA  
Tel: (678) 366-7887  
Fax: (678) 366-7717

Stonebranch, Inc.<sup>®</sup> makes no warranty, express or implied, of any kind whatsoever, including any warranty of merchantability or fitness for a particular purpose or use.

The information in this documentation is subject to change without notice.

Stonebranch shall not be liable for any errors contained herein or for incidental or consequential damages in connection with the furnishing, performance or use of this document.

All products mentioned herein are or may be trademarks of their respective owners.

© 2003-2010 by Stonebranch, Inc.

All rights reserved.



---

# Summary of Changes

---

**Changes for Universal Enterprise Controller 3.2.0 Reference Guide  
(uec-ref-3203)**  
**November 2, 2009**

#### **Universal Products 3.2.0.9**

- Removed information describing support of the zFS file system for Universal Enterprise Controller in [Chapter 2 Universal Enterprise Controller Configuration Options](#).

**Changes for Universal Enterprise Controller 3.2.0 Reference Guide  
(uec-ref-3202)**  
**September 8, 2009**

- Created this first version of the Universal Enterprise Controller 3.2.0 Reference Guide.

#### **Universal Enterprise Controller 3.2.0.4**

- Added the following configuration options in [Chapter 2 Universal Enterprise Controller Configuration Options](#):
  - [SAP\\_POLLING\\_INTERVAL](#)
  - [TMP\\_DIRECTORY](#)
  - [UNIX\\_DB\\_DATA\\_SET](#)
- Added the following code pages in Section [4.2 Character Code Pages](#):
  - IBM875
  - IBM4971

---

# Contents

---

<b>Summary of Changes .....</b>	<b>5</b>
<b>Contents .....</b>	<b>6</b>
<b>List of Tables .....</b>	<b>10</b>
<b>Preface .....</b>	<b>11</b>
Document Structure .....	11
Format .....	11
Conventions .....	12
Vendor References .....	13
Document Organization .....	14
<b>Chapter 1 Overview .....</b>	<b>15</b>
<b>Chapter 2 Universal Enterprise Controller Configuration Options.....</b>	<b>16</b>
2.1 Overview .....	16
2.2 Configuration Options Information .....	17
2.3 Configuration Options List .....	19
2.4 BKR_QUERIES_PER_THREAD .....	21
2.5 BKR_QUERY_THREADS .....	22
2.6 BKR_QUERY_TIMEOUT .....	23
2.7 CA_CERTIFICATES .....	24
2.8 CERTIFICATE .....	25
2.9 CERTIFICATE_REVOCATION_LIST .....	26

2.10 CODE_PAGE .....	27
2.11 COMM_SESSIONS_PER_THREAD .....	29
2.12 COMM_THREADS .....	30
2.13 COMMIT_COMPLETE_EXPIRATION .....	31
2.14 COMMIT_INCOMPLETE_EXPIRATION .....	32
2.15 CONVERT .....	33
2.16 DELETE_EVENTS_ON_BROKER .....	34
2.17 DNS_CACHE_TIMEOUT .....	35
2.18 DNS_POLLING_INTERVAL .....	36
2.19 HELP .....	37
2.20 HOSTNAME_RETRY_COUNT .....	38
2.21 JOB_THREADS .....	39
2.22 KEEP_MONITOR_EVENTS .....	40
2.23 LOG_MESSAGES .....	41
2.24 LOG_MESSAGES_DIRECTORY .....	42
2.25 LOGIN_ATTEMPTS .....	43
2.26 MESSAGE_DESTINATION .....	44
2.27 MESSAGE_LANGUAGE .....	45
2.28 MESSAGE_LEVEL .....	46
2.29 MONITOR_EVENT_EXPIRATION .....	47
2.30 MOUNT_POINT .....	49
2.31 MOUNT_POINT_MODE .....	50
2.32 PERSISTENT_EVENT_EXPIRATION .....	52
2.33 POLLING_INTERVAL .....	54
2.34 PRIVATE_KEY .....	55
2.35 PRIVATE_KEY_PWD .....	56
2.36 SAF_KEY_RING .....	57
2.37 SAF_KEY_RING_LABEL .....	58
2.38 SAP_POLLING_INTERVAL .....	59
2.39 SERVICE_IP_ADDRESS .....	60
2.40 SERVICE_PORT .....	61
2.41 SSL_CIPHER_LIST .....	62
2.42 SSL_IMPLEMENTATION .....	63
2.43 TMP_DIRECTORY .....	64

2.44 TRACE_DIRECTORY .....	65
2.45 TRACE_FILE_LINES .....	66
2.46 TRACE_TABLE .....	67
2.47 UPDATE_INTERVAL .....	69
2.48 USER_AUTHENTICATION_METHOD .....	70
2.49 VERSION .....	71
<b>Chapter 3 UECLoad Configuration Options .....</b>	<b>72</b>
3.1 Overview .....	72
3.2 Configuration Options Information .....	73
3.3 Configuration Options List .....	75
3.4 ADD .....	76
3.5 ARCFILE .....	77
3.6 BROKER_DEFFILE .....	78
3.7 BROKER_DESCRIPTION .....	79
3.8 BROKER_HOST .....	80
3.9 BROKER_NAME .....	81
3.10 BROKER_PORT .....	82
3.11 CODE_PAGE .....	83
3.12 COMMAND_FILE_ENCRYPTED .....	84
3.13 COMMAND_FILE_PLAIN .....	85
3.14 DELETE .....	86
3.15 ENCRYPTION_KEY .....	87
3.16 END_TIME .....	88
3.17 EXPORT .....	89
3.18 EXPORT_DELETE .....	90
3.19 FORMAT .....	91
3.20 HELP .....	92
3.21 LIST .....	93
3.22 MESSAGE_LEVEL .....	94
3.23 START_TIME .....	96
3.24 UEC_PORT .....	97
3.25 USER_ID .....	98
3.26 USER_PASSWORD .....	99

3.27 VERSION .....	100
<b>Chapter 4 Additional Information.....</b>	<b>101</b>
4.1 Overview .....	101
4.2 Character Code Pages .....	102
4.3 UTT Files .....	104
<b>Appendix A Customer Support .....</b>	<b>105</b>

---

# List of Tables

---

<b>Chapter 2 Universal Enterprise Controller Configuration Options . . . . .</b>	<b>16</b>
Table 2.1    Universal Enterprise Controller - Configuration Options .....	20
Table 2.2    UTT File Locations .....	28
Table 2.3    HFS Access Permission Modes .....	51
Table 2.4    SSL Cipher Suites (for CTL_SSL_CIPHER_LIST) .....	62
<b>Chapter 3 UECLoad Configuration Options . . . . .</b>	<b>72</b>
Table 3.1    UECLoad Configuration Options .....	75
<b>Chapter 4 Additional Information . . . . .</b>	<b>101</b>
Table 4.1    Universal Enterprise Controller - Additional Information .....	101
Table 4.2    Character Code Pages .....	103
Table 4.3    UTT File Locations .....	104

---

# Preface

---

## Document Structure

This document is written using specific conventions for text formatting and according to a specific document structure in order to make it as useful as possible for the largest audience. The following sections describe the document formatting conventions and organization.

## Format

---

Starting with Universal Products 3.2.0, Release 5, this Universal Enterprise Controller 3.2.0 Reference Guide serves as a companion document to the Universal Enterprise Controller 3.2.0 User Guide.

Links to detailed information in this reference guide have been created in the user guide.

In order for the links between these documents to work correctly:

- Place the documents in the same folder.
- In Adobe Reader / Adobe Acrobat, de-select **Open cross-document link in same window** in the **General** category of your **Preferences** dialog (selected from the **Edit** menu).

# Conventions

Specific text formatting conventions are used within this document to represent different information. The following conventions are used.

## Typeface and Fonts

This document provides tables that identify how information is used. These tables identify values and/or rules that are either pre-defined or user-defined:

- *Italics* denotes user-supplied information.
- **Boldface** indicates pre-defined information.

Elsewhere in this document, **This Font** identifies specific names of different types of information, such as file names or directories (for example, `\abc\123\help.txt`).

## Operating System-Specific Text

Most of this document describes the product in the context of all supported operating systems. At times, it is necessary to refer to operating system-specific information. This information is introduced with a special header, which is followed by the operating system-specific text in a different font size from the normal text.

### **z/OS**

This text pertains specifically to the z/OS line of operating systems.

This text resumes the information pertaining to all operating systems.

## Tips from the Stoneman



Look to the Stoneman for suggestions  
or for any other information  
that requires special attention.

### **Stoneman's Tip**

## Vendor References

---

References are made throughout this document to a variety of vendor operating systems. We attempt to use the most current product names when referencing vendor software.

The following names are used within this document:

- **z/OS** is synonymous with IBM z/OS and IBM OS/390 line of operating systems.
- **Windows** is synonymous with Microsoft's Windows 2000 / 2003 / 2008, Windows XP, Windows Vista, and Windows 7 lines of operating systems. Any differences between the different systems will be noted.
- **UNIX** is synonymous with operating systems based on AT&T and BSD origins and the Linux operating system.

Note: These names do not imply software support in any manner. For a detailed list of supported operating systems, see the Universal Products 3.2.0 Installation Guide.

# Document Organization

The document is organized into the following chapters:

- [Overview](#) (Chapter 1)  
Introduction to the reference information in this document.
- [Universal Enterprise Controller Configuration Options](#) (Chapter 2)  
Detailed information on all Universal Enterprise Controller configuration options for all operating systems.
- [UECLoad Configuration Options](#) (Chapter 3)  
Detailed information on all UECLoad configuration options for all operating systems.
- [Additional Information](#) (Chapter 4)  
Additional information related to Universal Enterprise Controller.
- [Customer Support](#) (Appendix A)  
Customer support contact information for Universal Enterprise Controller.

---

# Chapter 1

# Overview

---

The Universal Enterprise Controller 3.2.0 Reference Guide is a companion document to the Universal Enterprise Controller 3.2.0 User Guide.

It provides the following technical detail for the information and procedures presented in that document:

- Universal Enterprise Controller configuration options
- UECLoad configuration options
- Additional information

---

# Chapter 2

# Universal Enterprise Controller

# Configuration Options

---

## 2.1 Overview

This chapter provides detailed information on the configuration options available for use with the Universal Enterprise Controller.

The options are listed alphabetically, without regard to any specific operating system.

Information on how these options are used is documented in the Universal Command 3.2 User Guide.

Section [2.2 Configuration Options Information](#) provides a guideline for understanding the information presented for each option.

## 2.2 Configuration Options Information

For each configuration option, this chapter provides the following information.

### Description

Describes the configuration option and how it is used.

### Usage

Provides a table of the following information:

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	<Format / Value>					
Command Line Option, Long Form	<Format / Value>					
Configuration File Keyword	<Format / Value>					

### Method

Identifies the different methods used to specify Universal Enterprise Controller configuration options:

- Command Line Option, Short Form
- Command Line Option, Long Form
- Configuration File Keyword

Note: Each option can be specified using one or more methods.

## Syntax

Identifies the syntax of each method that can be used to specify the option:

- Format      Specific characters that identify the option.
- Value      Type of value(s) to be supplied for this method.

Note: If a Method is not valid for specifying the option, the Syntax field contains **n/a**.

## (Operating System)

Identifies (with a ✓ ) the operating systems for which each method of specifying the option is valid:

- OS/400
- HP NonStop
- UNIX
- Windows
- z/OS

---

## Values

Identifies all possible values for the specified value type.

Defaults are identified in **[bracketed bold type]**.

---

## <Additional Information>

Identifies any additional information specific to the option.

## 2.3 Configuration Options List

Table 2.1, below, identifies the Universal Enterprise Controller configuration options.

Option Name	Description	Page
BKR_QUERIES_PER_THREAD	Maximum number of simultaneous Broker queries allowed for each thread.	<a href="#">21</a>
BKR_QUERY_THREADS	Number of process threads started to initiate Broker queries during a polling cycle.	<a href="#">22</a>
BKR_QUERY_TIMEOUT	Period of time within which a Broker query must finish before timing out.	<a href="#">23</a>
CA_CERTIFICATES	UEC started task procedure ddname from which a PEM-formatted list of certificates is read.	<a href="#">24</a>
CERTIFICATE	UEC started task procedure ddname from which a PEM-formatted certificate is read.	<a href="#">25</a>
CERTIFICATE_REVOCATION_LIST	File name / ddname of the PEM-formatted CRL	<a href="#">26</a>
CODE_PAGE	Code page for text translation of network data.	<a href="#">27</a>
COMM_SESSIONS_PER_THREADS	Maximum number of UEC client sessions that can occur on each of the communications threads.	<a href="#">29</a>
COMM_THREADS	Number of threads created to perform communications between UEC and the UEC client applications.	<a href="#">30</a>
COMMIT_COMPLETE_EXPIRATION	Deletes completed commit configurations, by age.	<a href="#">31</a>
COMMIT_INCOMPLETE_EXPIRATION	Deletes incomplete commit configurations, by age	<a href="#">32</a>
CONVERT	Converts a pre-3.2.0 database into the current database format.	<a href="#">33</a>
DELETE_EVENTS_ON_BROKER	Specification for whether or not events are deleted on the Universal Broker after they are retrieved and put into the UEC events database.	<a href="#">34</a>
DNS_CACHE_TIMEOUT	Length of time to retain a resolved host name in memory cache.	<a href="#">35</a>
DNS_POLLING_INTERVAL	Time interval at which the DNS cache is polled.	<a href="#">36</a>
HELP	Write options help to SYSPRINT ddname.	<a href="#">37</a>
HOSTNAME_RETRY_COUNT	Number of times that UEC will attempt to resolve the host name of a specified Universal Broker before it ends with a connect error.	<a href="#">38</a>
JOB_THREADS	Number of threads created to perform internal tasks in UEC.	<a href="#">39</a>
KEEP_MONITOR_EVENTS	Specification for whether or not monitor events are written into the UEC temporary database.	<a href="#">40</a>
LOG_MESSAGES	Specification for whether or not to log all XML message traffic between UEC and any connected applications.	<a href="#">41</a>
LOG_MESSAGES_DIRECTORY	Directory used for UEC log messages.	<a href="#">42</a>
LOGIN_ATTEMPTS	Number of failed login attempts allowed by a user before being disconnected by UEC.	<a href="#">43</a>

Option Name	Description	Page
MESSAGE_DESTINATION	Location to which messages are written.	<a href="#">44</a>
MESSAGE_LANGUAGE	Language used for messages.	<a href="#">45</a>
MESSAGE_LEVEL	Level of messages written.	<a href="#">46</a>
MONITOR_EVENT_EXPIRATION	Length of time that state data is retained in the UEC database.	<a href="#">47</a>
MOUNT_POINT	HFS directory in which the HFS database allocated to ddname <b>UNVDB</b> is mounted.	<a href="#">49</a>
MOUNT_POINT_MODE	HFS access permission mode value with which the mounted database file system's root directory is set.	<a href="#">50</a>
PERSISTENT_EVENT_EXPIRATION	Deletes event records, by age.	<a href="#">52</a>
POLLING_INTERVAL	Time interval at which agents are polled.	<a href="#">54</a>
PRIVATE_KEY	UEC started task procedure ddname from which a PEM-formatted private key is read.	<a href="#">55</a>
PRIVATE_KEY_PWD	Password for the PRIVATE_KEY.	<a href="#">56</a>
SAF_KEY_RING	SAF certificate key ring name.	<a href="#">57</a>
SAF_KEY_RING_LABEL	SAF certificate key ring label.	<a href="#">58</a>
SAP_POLLING_INTERVAL	Interval (in seconds) at which the SAP systems are polled for their status and job activity.	<a href="#">59</a>
SERVICE_IP_ADDRESS	IP interface from which to accept connections.	<a href="#">60</a>
SERVICE_PORT	Port from which to accept connections.	<a href="#">61</a>
SSL_CIPHER_LIST	SSL cipher suite to be used for network communications.	<a href="#">62</a>
SSL_IMPLEMENTATION	SSL implementation to be used for network configuration.	<a href="#">63</a>
TMP_DIRECTORY	HFS directory in which Universal Enterprise Controller creates temporary files.	<a href="#">64</a>
TRACE_DIRECTORY	Directory used for UEC trace files	<a href="#">65</a>
TRACE_FILE_LINES	Maximum number of lines written to the trace ddname.	<a href="#">66</a>
TRACE_TABLE	Size of the trace table.	<a href="#">67</a>
UPDATE_INTERVAL	Time interval at which connected Universal Activity Monitor clients are updated.	<a href="#">69</a>
USER_AUTHENTICATION_METHOD	Authentication method to be used when authenticating UEC user accounts.	<a href="#">70</a>
VERSION	Writes the program version and copyright statement.	<a href="#">71</a>

Table 2.1 Universal Enterprise Controller - Configuration Options

## 2.4 BKR\_QUERIES\_PER\_THREAD

### Description

---

The BKR\_QUERIES\_PER\_THREAD option specifies the maximum number of simultaneous Broker queries allowed for each thread.

For example, if there are 4 threads and 25 queries per thread allowed, then a maximum of 100 Brokers can be queried at the same time during one polling cycle.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	bkr_queries_per_thread <i>count</i>				✓	✓

### Values

---

*count* is the maximum number of queries allowed.

#### Default

**Windows**

[Default is 10.]

**z/OS**

[Default is 25.]

## 2.5 BKR\_QUERY\_THREADS

### Description

---

The BKR\_QUERY\_THREADS option specifies the number of threads started in order to initiate broker queries during a polling cycle.

Note: One BKR\_QUERY\_THREADS is equivalent to one task or TCB.

#### **z/OS**

On z/OS, for each query thread, a task (TCB) is created in the UEC address space. A task is an individually dispatchable unit of work within the address space. The more tasks that exist in the address space, the more CPU and memory resources the address space consumes. The benefit of the additional tasks is that each task may execute in parallel producing a higher overall throughput of broker queries.

The throughput benefits achieved with additional tasks diminish after a certain optimum number of tasks. The optimum number depends on the hardware resources available to the operating system and the UEC address space resource configuration. A typical range is from 2 to 10 threads.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	bkr_query_threads <i>count</i>				✓	✓

### Values

---

*count* is the number of threads started in order to initiate broker queries.

#### Default

#### **Windows**

[Default is 10.]

#### **z/OS**

[Default is 4.]

## 2.6 BKR\_QUERY\_TIMEOUT

### Description

---

The BKR\_QUERIES\_TIMEOUT option specifies the time in which a broker query must finish before timing out.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	bkr_query_timeout <i>count</i>				✓	✓

### Values

---

*count* is the time (in seconds) in which a broker query must finish.

**[Default is 60.]**

## 2.7 CA\_CERTIFICATES

### Description

---

The CA\_CERTIFICATES option specifies the PEM-formatted trusted Certificate Authority (CA) X.509 certificates file / ddname.

Trust CA certificates are required if certificate authentication and verification is desired.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-ca_certs <i>ddname</i> or <i>file</i>					✓
Configuration File Keyword	ca_certificates <i>ddname</i> or <i>file</i>				✓	✓

### Values

---

#### **z/OS**

*ddname* is the ddname of the X.509 certificates.

#### **Windows**

*file* is the path name of the X.509 certificates file. Relative paths are relative the current working directory.

## 2.8 CERTIFICATE

### Description

---

The CERTIFICATE option specifies the file / ddname name of the PEM-formatted X.509 certificate that identifies the Universal Enterprise Controller.

UEC may use an X.509 certificate to identify itself when connecting to Universal Brokers. If a certificate is not specified by CERTIFICATE, an internal certificate is generated.

Note: If the CERTIFICATE option is used, the [PRIVATE\\_KEY](#) option also is required.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-cert <i>ddname or file</i>					✓
Configuration File Keyword	certificate <i>ddname or file</i>				✓	✓

### Values

---

#### **z/OS**

*ddname* is the ddname of the X.509 certificate.

#### **Windows**

*file* is the path name of the X.509 certificate file. Relative paths are relative to the current working directory.

## 2.9 CERTIFICATE\_REVOCATION\_LIST

### Description

---

The CERTIFICATE\_REVOCATION\_LIST option specifies the file name / ddname of the PEM-formatted file containing the Certificate Revocation List (CRL) issued by the trusted Certificate Authority.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-crl <i>file or ddname</i>					✓
Configuration File Keyword	crl <i>file or ddname</i>				✓	✓

### Values

---

#### **z/OS**

*ddname* is the ddname of the file containing the CRL. The value is used only when the [SSL\\_IMPLEMENTATION](#) option is set to *OPENSSL*.

#### **Windows**

*file* is the path name of the file containing the CRL. Relative paths are relative to the current working directory.

## 2.10 CODE\_PAGE

### Description

---

The CODE\_PAGE option specifies the character code page that is used to translate text data received and transmitted over the network.

The Universal Translate Table (UTT) files are used to translate between Unicode and the local single-byte code page.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	<code>-t codepage</code>					✓
Command Line Option, Long Form	<code>-codepage codepage</code>					✓
Configuration File Keyword	<code>codepage codepage</code>				✓	✓

### Value

---

*codepage* is the character code page that is used to translate data. It is based on its Universal Translate Table (UTT) file name (see [Table 2.2](#)).

UTT files are used to translate between Unicode and the local single-byte code page. (All UTT files end with an extension of `.utt`.)

### Default

#### Windows

[Default is **ISO8859-1**.]

#### z/OS

[Default is **IBM1047**.]

## UTT Files

Universal Translate Table (UTT) files are used to translate between Unicode and the local single-byte code page.

Operating System	UTT File Location
z/OS	UTT files are members of the PDS allocated to the Broker ddname <b>UNVNLS</b> . <i>codepage</i> specifies the member name.
Windows	UTT files are located in the <b>NLS</b> subdirectory of the installation directory. <i>codepage</i> is the base file name of the UTT file.

Table 2.2 UTT File Locations

## 2.11 COMM\_SESSIONS\_PER\_THREAD

### Description

---

The COMM\_SESSIONS\_PER\_THREAD option specifies the maximum number of UEC client sessions that can occur on each of the communications threads (see the [COMM\\_THREADS](#) option).

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	comm_sessions_per_thread <i>count</i>				✓	✓

### Value

---

*count* is the number of sessions per communications thread.

**[Default is 64.]**

## 2.12 COMM\_THREADS

### Description

---

The COMM\_THREADS option specifies the number of threads created to perform communications between UEC and the UEC client applications.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	comm_threads <i>count</i>				✓	✓

### Value

---

*count* is the number of threads.

**[Default is 1.]**

## 2.13 COMMIT\_COMPLETE\_EXPIRATION

### Description

---

The COMMIT\_COMPLETE\_EXPIRATION option specifies the length of time that complete commit records are retained, upon which (or after which) UEC deletes them.

The minimum length of time that records are retained is one hour.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	commit_complete_expiration <i>time</i>				✓	✓

### Value

---

*time* is the length of time that completed commit records are retained before being deleted.

Valid values for *time* are a number followed by (optionally) one of the following suffixes:

- **s** (seconds)
- **m** (minutes)
- **h** (hours)
- **d** (days)

If a suffix is not specified, the number is assumed to indicate seconds.

(For example, if **3d** is specified, the records are retained for three days before UEC deletes them.)

Note: If **0** is specified, completed commit records are not deleted.

**[Default is 60d.]**

## 2.14 COMMIT\_INCOMPLETE\_EXPIRATION

### Description

---

The COMMIT\_INCOMPLETE\_EXPIRATION option specifies the length of time that incomplete commit records are retained, upon which (or after which) UEC deletes them.

The minimum length of time that records are retained is one hour.

Note: An incomplete commit record is a committed configuration with agents that are pending to receive the configuration changes.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	commit_incomplete_expiration <i>time</i>				✓	✓

### Value

---

*time* is the length of time that incomplete commit records are retained before being deleted.

Valid values for *time* are a number followed by (optionally) one of the following suffixes:

- **s** (seconds)
- **m** (minutes)
- **h** (hours)
- **d** (days)

If a suffix is not specified, the number is assumed to indicate seconds.

(For example, if **3d** is specified, the records are retained for three days before UEC deletes them.)

Note: If **0** is specified, incomplete commit records are not deleted.

**[Default is 90d.]**

## 2.15 CONVERT

### Description

---

The CONVERT option converts a pre-3.2.0 database into the current database format.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-convert					✓
Configuration File Keyword	n/a					

### Value

---

(There are no values for this option.)

## 2.16 DELETE\_EVENTS\_ON\_BROKER

### Description

---

The DELETE\_EVENTS\_ON\_BROKER option specifies whether or not events are deleted on the Universal Broker after they are retrieved and put into the UEC events database.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	delete_events_on_broker <i>option</i>				✓	✓

### Value

---

*option* is the specification for whether or not to delete events on the Universal Broker.

Valid values for *option* are:

- **yes**  
Delete events on the Universal Broker.
- **no**  
Do not delete events on the Universal Broker.

**[Default is no.]**

## 2.17 DNS\_CACHE\_TIMEOUT

### Description

---

The DNS\_CACHE\_TIMEOUT option specifies the length of time (in seconds) to retain a resolved host name in DNS memory cache.

The DNS cache provides a performance enhancement in environments where the DNS system is slow to respond.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	dns_cache_timeout <i>seconds</i>				✓	✓

### Value

---

*seconds* is the number of seconds to retain the host name in memory cache.

A value of **0** disables caching of host entries.

**[Default is 360.]**

## 2.18 DNS\_POLLING\_INTERVAL

### Description

---

The DNS\_POLLING\_INTERVAL option specifies the time interval (in seconds) at which the DNS cache is polled.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	dns_polling_interval <i>seconds</i>				✓	✓

### Value

---

*seconds* is the interval (in seconds) at which the DNS cache is polled.

**[Default is 120.]**

## 2.19 HELP

### Description

---

The HELP option writes a description of the command options and their format.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	-h					✓
Command Line Option, Long Form	-help					✓
Configuration File Keyword	n/a					

### Value

---

(There are no values for the HELP option.)

## 2.20 HOSTNAME\_RETRY\_COUNT

### Description

---

The HOSTNAME\_RETRY\_COUNT option specifies the number of times that UEC will attempt to resolve the host name of a specified Universal Broker before it ends with a connect error.

UEC will sleep for one second between resolution attempts.

Connection errors occur for several reasons. A common reason is a failure to resolve the Universal Broker host name specified with the [BROKER\\_HOST](#) option. This error can occur intermittently due to a temporary resource shortage or a temporary DNS problem. If your system is prone to host name resolution errors, it may help to have UEC retry the connection several times.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-hostname_retry_count <i>count</i>					✓
Configuration File Keyword	hostname_retry_count <i>count</i>				✓	✓

### Values

---

*count* is the number of times that UEC will attempt to resolve the host name.

**[Default is 1.]**

## 2.21 JOB\_THREADS

### Description

---

The JOB\_THREADS option specifies the number of threads created to perform internal tasks in UEC.

These tasks can include processing for UEC client applications where this value can affect the performance of client applications.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	job_threads <i>count</i>				✓	✓

### Value

---

*count* is the number of threads.

**[Default is 10.]**

## 2.22 KEEP\_MONITOR\_EVENTS

### Description

---

The KEEP\_MONITOR\_EVENTS option specifies whether or not monitor events are written into the UEC temporary database.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-keep_monitor_events <i>option</i>					✓
Configuration File Keyword	keep_monitor_events <i>option</i>				✓	✓

### Values

---

*option* is the specification for whether or not to write monitor events into the database.

Valid values for *option* are:

- **yes**  
Write monitor events into the UEC temporary database.
- **no**  
Do not write monitor events into the UEC temporary database.

**[Default is no.]**

Note: KEEP\_MONITOR\_EVENTS should be set to the default value unless directed otherwise by Stonebranch, Inc. [Customer Support](#).

## 2.23 LOG\_MESSAGES

### Description

---

The LOG\_MESSAGES option specifies whether or not to write to a log all XML messages exchanged between UEC and any connected applications.

Note: LOG\_MESSAGES is a debugging flag to be used with help from Stonebranch, Inc. [Customer Support](#).

**z/OS**

Log messages are written to the UNVMSGS and UNVPRSR ddnames.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	log_messages <i>option</i>				✓	✓

### Value

---

*option* is the specification for whether or not to write the messages.

Valid values for *option* are:

- **yes**  
Write XML message traffic to a log.
- **no**  
Do not write XML message traffic to a log.

## 2.24 LOG\_MESSAGES\_DIRECTORY

### Description

---

The LOG\_MESSAGES\_DIRECTORY option specifies the directory that UEC uses for log messages.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	log_messages_directory <i>directory</i>				✓	

### Value

---

*directory* is the directory to use for log messages.

**[Default is c:\program files\universal\uectr\log.]**

## 2.25 LOGIN\_ATTEMPTS

### Description

---

The LOGIN\_ATTEMPTS option specifies the number of failed login attempts over a single connection that a user is allowed before UEC disconnects the user.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	login_attempts <i>count</i>				✓	✓

### Values

---

*count* is the number of failed login attempts allowed.

Valid values for *count* are any number.

**[Default is 3.]**

## 2.26 MESSAGE\_DESTINATION

### Description

The MESSAGE\_DESTINATION option specifies the location where messages are written.

### Usage

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	<code>-d destination</code>					✓
Command Line Option, Long Form	<code>-dest destination</code>					✓
Configuration File Keyword	<code>message_dest destination</code>				✓	✓

### Value

*destination* is the location where messages are written.

Valid values for *destination* are:

#### **z/OS**

- **stderr**  
Writes the messages to the console.  
**stderr** is a valid value only if UEC is running as a console application.
- **logfile**  
Writes the messages to ddname **UNVLOG**.
- **system**  
Writes the messages to the console as WTO messages.

**[Default for a console process is stderr.]**

#### **Windows**

- **system**  
Writes the messages to the Windows Application Event Log.

## 2.27 MESSAGE\_LANGUAGE

### Description

---

The MESSAGE\_LANGUAGE option specifies the Universal Message Catalog (UMC) that is used to format messages.

There is a message catalog for each language.

Universal Enterprise Controller message catalog member / file names start with characters UECMC. The first three characters of the language are used as a three-character suffix of the member / file name. All UMC catalogs have a .UMC extension

Note: Currently, the only message catalog provided is for English.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	-L <i>language</i>					✓
Command Line Option, Long Form	-lang <i>language</i>					✓
Configuration File Keyword	language <i>language</i>				✓	✓

### Values

---

*language* is the name of the UMC catalog.

**z/OS**

*language* translates to a member name of the library allocated on the UNVNLS DD statement.

**[Default is ENGLISH.]**

## 2.28 MESSAGE\_LEVEL

### Description

The MESSAGE\_LEVEL option specifies the level of messages to write.

### Usage

Method	Syntax *	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	-l <i>level</i>					✓
Command Line Option, Long Form	-level <i>level</i>					✓
Configuration File Keyword	message_level <i>level</i>				✓	✓

### Values

*level* is the level of messages to write.

Valid values for *level* are:

- **trace**  
Writes trace messages used for diagnostic purposes.  
Note: Use **trace** only as directed by Stonebranch, Inc. [Customer Support](#).
- **audit**  
Writes audit, informational, warning, and error messages.
- **info**  
Writes informational, warning, and error messages.
- **warn**  
Writes warning and error messages.
- **error**  
Writes error messages only.

**[Default is info.]**

## 2.29 MONITOR\_EVENT\_EXPIRATION

### Description

---

The MONITOR\_EVENT\_EXPIRATION option specifies the length of time that state data is retained in the UEC database.

State data refers to data collected and generated by UEC that is used to represent the work and working state of Universal Products at a point in time. Collected data includes monitor-routed UES events and Universal Products component state data.

Each state data record is associated with a particular Universal Product workflow. While the workflow is active, some component of the workflow is generating state data. State data is aged and expired at the workflow level.

All records associated with a workflow are considered to be as old as the last update performed for the workflow. Therefore, when a clean-up cycle occurs, and no state data activity has occurred on a workflow for at least the length of time specified by MONITOR\_EVENT\_EXPIRATION, all records associated with the workflow are removed from the database.

State data clean-up cycles occur once every hour. Therefore, the minimum length of time that state data is retained is one hour.

## Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	monitor_event_expiration <i>time</i>				✓	✓

## Values

---

*time* is the length of time that event records are retained before being deleted.

Valid values for *time* are a number followed by (optionally) one of the following suffixes:

- **s** (seconds)
- **m** (minutes)
- **h** (hours)
- **d** (days)

If a suffix is not specified, the number is assumed to indicate seconds.

(For example, if **3d** is specified, the records are retained for three days before UEC deletes them.)

**[Default is 24h.]**

## 2.30 MOUNT\_POINT

### Description

---

The MOUNT\_POINT option specifies the HFS directory in which the HFS database allocated to ddname UNVDB is mounted.

The actual mount point will be a subdirectory named after the HFS data set name being mounted.

If the mount point does not exist, it is created by UEC.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-mount_point <i>directory</i>					✓
Configuration File Keyword	mount_point <i>directory</i>					✓

### Values

---

*directory* is the HFS directory in which the HFS database is mounted.

**[Default is /tmp.]**

Note: The HFS permission mode is set to *dir*.

## 2.31 MOUNT\_POINT\_MODE

### Description

---

The MOUNT\_POINT option specifies the HFS access permission mode value with which the mounted database file system's root directory is set.

The HFS database file system is initialized only if the file `.initd` is not found in the root directory. When initialization is performed once, `.initd` is created; initialization will not be performed again.

If you need to customize the directory ownership or permissions, define the file `.initd` in the file system's root directory; UEC will not perform its initialization.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	<code>-mount_point_mode mode</code>					✓
Configuration File Keyword	<code>mount_point_mode mode</code>					✓

## Values

*mode* is the HFS permission mode value, which is a sum of the permission modes to be granted.

[Table 2.3](#), below, describes each mode.

Mode	Description
100	User execute permission
200	User write permission
400	User read permission
010	Group execute permission
020	Group write permission
040	Group read permission
001	Other execute permission
002	Other write permission
004	Other read permission

Table 2.3 HFS Access Permission Modes

The format of *mode* is the same as the “change mode” USS command **chmod**. It is an octal number that specifies the permission mode value corresponding to the user, group, and other permission mode fields.

(Refer to the IBM *UNIX System Services Command Reference* for complete details on the **chmod** command.)

**Default is 750, which specifies:**

- **Read-write-execute access for the user**
- **Read-execute access for the group**
- **No access for other**

## 2.32 PERSISTENT\_EVENT\_EXPIRATION

### Description

---

The PERSISTENT\_EVENT\_EXPIRATION option specifies the length of time that persistent event records are retained in the UEC database.

Persistent event data refers to data collected and generated by UEC from the Universal Broker on remote platforms. This data is used to represent a sequence of events that have occurred over a period of time. Collected data includes persistent-routed UES events. This commonly is referred to as Universal Event Subsystem data.

The minimum length of time that records are retained is one hour.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	persistent_event_expiration <i>time</i>				✓	✓

## Value

---

*time* is the length of time that persistent event records are retained before being deleted.

Valid values for *time* are a number followed by (optionally) one of the following suffixes:

- **s** (seconds)
- **m** (minutes)
- **h** (hours)
- **d** (days)

If a suffix is not specified, the number is assumed to indicate seconds.

(For example, if **3d** is specified, the records are retained for three days before UEC deletes them.)

Note: If **0** is specified, persistent event records are not deleted.

**[Default is 60d.]**

## 2.33 POLLING\_INTERVAL

### Description

---

The POLLING\_INTERVAL option specifies the time interval (in seconds) at which the agents in the UEC agent list are polled.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	polling_interval <i>seconds</i>				✓	✓

### Value

---

*seconds* is the interval (in seconds) at which the agents are polled.

Valid values for *seconds* is any number.

**[Default is 120.]**

If your agent list is large, you may want to increase this default interval.

Note: POLLING\_INTERVAL should not be set to a value lower than the number of agents divided by [BKR\\_QUERIES\\_PER\\_THREAD x BKR\\_QUERY\\_THREADS](#). While doing so will not cause any harm to UEC, it will prevent UEC from operating as efficiently as possible.

## 2.34 PRIVATE\_KEY

### Description

---

The PRIVATE\_KEY option specifies the location of the PEM-formatted private key that corresponds to the X.509 certificate specified by the [CERTIFICATE](#) option.

Note: PRIVATE\_KEY is required only if a certificate is specified by [CERTIFICATE](#).

### Usage

---

Method	Syntax *	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-private_key <i>ddname</i>					✓
Configuration File Keyword	private_key <i>ddname</i> or <i>file</i>				✓	✓

### Values

---

#### **z/OS**

*ddname* is the ddname from which the PEM-formatted private key is read.

#### **Windows**

*file* is the full path name of the file from which the PEM-formatted private key is read.

## 2.35 PRIVATE\_KEY\_PWD

### Description

---

The PRIVATE\_KEY\_PWD option specifies the password for the PEM-formatted private key specified with the [PRIVATE\\_KEY](#) option.

Note: Whether or not the password is required depends on whether or not it is required by the private key.

### Usage

---

Method	Syntax *	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-private_key_pwd <i>password</i>					✓
Configuration File Keyword	private_key_password <i>password</i>				✓	✓

### Values

---

*password* is the password for the private key.

## 2.36 SAF\_KEY\_RING

### Description

---

The SAF\_KEY\_RING option specifies the name of the SAF key ring that a UEC will use as its X.509 certificate, if Universal Broker requires the UEC to provide an X.509 certificate to identify itself to the Broker.

Note: SAF\_KEY\_RING is required if the [SSL\\_IMPLEMENTATION](#) option is set to *SYSTEM*.

### Usage

---

Method	Syntax *	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-saf_key_ring <i>name</i>					✓
Configuration File Keyword	saf_key_ring <i>name</i>					✓

### Values

---

*name* is the name of the SAF certificate key ring.

## 2.37 SAF\_KEY\_RING\_LABEL

### Description

---

The SAF\_KEY\_RING\_LABEL option specifies the label of the certificate in the SAF certificate key ring.

(The key ring is specified by the [SAF\\_KEY\\_RING](#) option.)

### Usage

---

Method	Syntax *	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-saf_key_ring_label <i>label</i>					✓
Configuration File Keyword	saf_key_ring_label <i>label</i>					✓

### Values

---

*label* is the label of the SAF certificate key ring.

**[Default is the default certificate in the key ring.]**

## 2.38 SAP\_POLLING\_INTERVAL

### Description

---

The SAP\_POLLING\_INTERVAL option specifies the interval (in seconds) at which the SAP systems are polled for their status and job activity.

### Usage

---

Method	Syntax *	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	sap_polling_interval <i>interval</i>				✓	✓

### Values

---

*interval* is the interval (in seconds) at which the SAP systems are polled for their status and job activity.

**{Default is 120.]**

## 2.39 SERVICE\_IP\_ADDRESS

### Description

The SERVICE\_IP\_ADDRESS option specifies the IP interface on which to accept network connection requests.

SERVICE\_IP\_ADDRESS is useful only if the system has multiple IP interfaces.

If the system has multiple interfaces and SERVICE\_IP\_ADDRESS is not used, connection requests are accepted on all interfaces defined on the system.

If the system has only one interface, do not use SERVICE\_IP\_ADDRESS.

### Usage

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	-i <i>ipaddress</i>					✓
Command Line Option, Long Form	-svcipaddr <i>ipaddress</i>					✓
Configuration File Keyword	service_ip_address <i>ipaddress</i>				✓	✓

### Values

*ipaddress* is the IP address on which to accept network connection requests.

Valid values for *ipaddress* are:

- Dotted numeric format (for example, **20.30.40.50**)
- Domain name format (for example, **myinterface**).

Note: An asterisk ( \* ) specifies all interfaces.

**z/OS**

[Default is \*.]

## 2.40 SERVICE\_PORT

### Description

---

The SERVICE\_PORT option specifies the IP port on which to accept network connection requests.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	<code>-p <i>port</i></code>					✓
Command Line Option, Long Form	<code>-svcpport <i>port</i></code>					✓
Configuration File Keyword	<code>service_port <i>port</i></code>				✓	✓

### Values

---

*port* is the IP port on which to accept network connection requests.

Valid values for *port* are:

- Numeric value (for example, **7000**)
- Service name (for example, **uectlrv**)

**[Default is 8778.]**

Note: It is recommended that the default value be used, if possible.

## 2.41 SSL\_CIPHER\_LIST

### Description

The SSL\_CIPHER\_LIST option specifies one or more SSL cipher suites that are acceptable to use for network communications between UEC components.

### Usage

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-ssl_cipher_list <i>cipherlist</i>					✓
Configuration File Keyword	ssl_cipher_list <i>cipherlist</i>				✓	✓

### Values

*cipherlist* is a comma-separated list of SSL cipher suites. The list should be ordered with the most preferred suite first and the least preferred suite last.

Table 2.4 identifies the list of SSL cipher suites supported for this option.

Cipher Suite	Description
RC4-SHA	128-bit RC4 encryption and SHA-1 message digest
RC4-MD5	128-bit RC4 encryption and MD5 message digest
AES256-SHA	256-bit AES encryption and SHA-1 message digest
AES128-SHA	128-bit AES encryption and SHA-1 message digest
DES-CBC3-SHA	128-bit Triple-DES encryption and SHA-1 message digest
DES-CBC-SHA	128-bit DES encryption and SHA-1 message digest

Table 2.4 SSL Cipher Suites (for CTL\_SSL\_CIPHER\_LIST)

[Default is RC4-SHA,RC4-MD5,AES256-SHA,AES128-SHA,DES-CBC3-SHA, DES-CBC-SHA.]

## 2.42 SSL\_IMPLEMENTATION

### Description

---

The SSL\_IMPLEMENTATION option specifies the Secure Socket Layer (SSL) implementation to be used for network communications.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-ssl_implementation <i>option</i>					✓
Configuration File Keyword	ssl_implementation <i>option</i>					✓

### Values

---

*option* is the SSL implementation to be used.

Valid values for option are:

- **openssl**  
OpenSSL SSL library is used for the SSL protocol.
- **system**  
z/OS System SSL library is used for the SSL protocol. The z/OS System SSL library has installation and configuration prerequisites. (See the Universal Products 3.2.0 Installation Guide for a description of the prerequisites before using System SSL.)

**[Default is openssl.]**

## 2.43 TMP\_DIRECTORY

### Description

---

The TMP\_DIRECTORY option specifies the HFS directory in which Universal Enterprise Controller creates temporary files.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	tmp_directory <i>directory</i>					✓

### Values

---

*directory* is the name of the directory for temporary files. A fully qualified path name must be specified.

**[Default is tmp\_directory /tmp.]**

## 2.44 TRACE\_DIRECTORY

### Description

---

The TRACE\_DIRECTORY option specifies the directory that the Universal Enterprise Controller uses for trace files.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	trace_directory <i>directory</i>				✓	

### Values

---

*directory* is the name of the directory for trace files.

**[Default is c:\Program Files\Universal\uectr.]**

## 2.45 TRACE\_FILE\_LINES

### Description

---

The TRACE\_FILE\_LINES option specifies the maximum number of lines to write to the trace file.

A trace file is generated when the [MESSAGE\\_LEVEL](#) option is set to *TRACE*. The trace file will wrap around when the maximum number of lines has been reached and start writing trace entries after the trace header lines.

(The average size of a trace file line is 50 characters.)

#### **z/OS**

The trace file is written to ddname UNVTRACE. However, TRACE\_FILE\_LINES has no effect if ddname UNVTRACE has allocated a JES SYSOUT file.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-tracefilelines <i>lines</i>					✓
Configuration File Keyword	trace_file_lines <i>lines</i>				✓	✓

### Values

---

*lines* is the maximum number of lines to write to the trace file.

**[Default is 50,000.]**

## 2.46 TRACE\_TABLE

### Description

---

The TRACE\_TABLE option specifies the size of a wrap-around trace table maintained in memory.

The trace table is written to a file / data set when the program ends under the conditions specified in this option. Tracing is activated, and a trace file is generated, when the [MESSAGE\\_LEVEL](#) option is set to *TRACE*.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	trace_table <i>size</i> , <i>condition</i>				✓	✓

### Values

---

*size* is the size (in bytes) of the trace table.

The size can be suffixed with either of the following characters:

- **M** indicates that the size is specified in megabytes
- **K** indicates that the size is specified in kilobytes

For example, **50M** indicates that 50 X 1,048,576 bytes of memory is allocated for the trace table.

Note: If *size* is **0**, the trace table is not used.

**[Default is 0.]**

*condition* is the condition under which the trace table is written.

Possible values for *condition* are:

- **error**  
Write the trace table if the program ends with a non-zero exit code.
- **always**  
Write the trace table when the program ends regardless of the exit code.
- **never**  
Never write the trace table.

**[Default is *never*.]**

## 2.47 UPDATE\_INTERVAL

### Description

---

The UPDATE\_INTERVAL option specifies the time interval (in seconds) at which connected Universal Activity Monitor clients are updated.

When a change is made to the broker or group lists through the UEC Administration application, the change will not be committed until the end of the specified interval. If additional changes are made within that interval, all changes made during the interval will be committed at the same time.

When the changes are committed, all connected Universal Activity Monitor clients will be updated with the new information. This will minimize message traffic to existing Universal Activity Monitor clients during mass UEC Administration updates.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	update_interval <i>seconds</i>				✓	✓

### Values

---

*seconds* is the time interval at which clients are updated.

**[Default is 120.]**

## 2.48 USER\_AUTHENTICATION\_METHOD

### Description

---

The USER\_AUTHENTICATION\_METHOD option specifies the authentication method to be used when authenticating UEC user accounts.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	n/a					
Configuration File Keyword	user_authentication_method <i>method</i>				✓	✓

### Values

---

*method* is the authentication method to be used.

Valid values for *method* are:

- **uec**  
Use UEC authentication only
- **os**  
Use the native operating system authentication method where UEC is running.
- **uec,os**  
Use both UEC authentication and native operating system authentication

**[Default is UEC, OS.]**

## 2.49 VERSION

### Description

---

The VERSION option instructs UEC to write program version and copyright information.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	-v					✓
Command Line Option, Long Form	-version					✓
Configuration File Keyword	n/a					

### Value

---

(There are no values for this option.)

---

# Chapter 3

# UECLoad

# Configuration Options

---

## 3.1 Overview

This chapter provides detailed information on the configuration options available for use with the UECLoad utility. Section [3.2 Configuration Options Information](#) provides a guideline for understanding the information presented for each option.

The options are listed alphabetically, without regard to any specific operating system.

Information on how these options are used is documented in [Chapter 5 UECLoad Utility](#).

## 3.2 Configuration Options Information

For each configuration option, this chapter provides the following information.

### Description

Describes the configuration option and how it is used.

### Usage

Provides a table of the following information:

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	<Format / Value>					
Command Line Option, Long Form	<Format / Value>					
Environment Variable	<Format / Value>					
Definition File Keyword	<Format / Value>					

### Method

Identifies the different methods used to specify UECLoad configuration options:

- Command Line Option, Short Form
- Command Line Option, Long Form
- Environment Variable
- Definition File Keyword

Note: Each option can be specified using one or more methods.

## Syntax

Identifies the syntax of each method that can be used to specify the option:

- Format      Specific characters that identify the option.
- Value      Type of value(s) to be supplied for this method.

Note: If a Method is not valid for specifying the option, the Syntax field contains **n/a**.

## (Operating System)

Identifies (with a ✓ ) the operating systems for which each method of specifying the option is valid:

- OS/400
- HP NonStop
- UNIX
- Windows
- z/OS

## Values

Identifies all possible values for the specified value type.

Defaults are identified in **[bracketed bold type]**.

## <Additional Information>

Identifies any additional information specific to the option.

### 3.3 Configuration Options List

[Table 3.1](#), below, identifies all UECLoad configuration options.

Option	Description	Page
ADD	Specification to add broker definitions to the UEC.	<a href="#">76</a>
ARCFILE	Archived file to retrieve for export.	<a href="#">77</a>
BROKER_DEFFILE	File containing multiple broker definitions to be added or deleted in the UEC database.	<a href="#">78</a>
BROKER_DESCRIPTION	Description of the defined Universal Broker.	<a href="#">79</a>
BROKER_HOST	TCP/IP host name of the defined Universal Broker.	<a href="#">80</a>
BROKER_NAME	Unique name of the defined Universal Broker.	<a href="#">81</a>
BROKER_PORT	TCP/IP port number of the defined Universal Broker.	<a href="#">82</a>
CODE_PAGE	Code page used for text translation.	<a href="#">83</a>
COMMAND_FILE_ENCRYPTED	Encrypted command file.	<a href="#">84</a>
COMMAND_FILE_PLAIN	Plain text command file.	<a href="#">85</a>
DELETE	Specification to delete broker definitions from the UEC.	<a href="#">86</a>
ENCRYPTION_KEY	Encryption key used to decrypt an encrypted command file specified by COMMAND_FILE_ENCRYPTED.	<a href="#">87</a>
END_TIME	End time of exported data	<a href="#">88</a>
EXPORT	Specification to output the described broker definition in a format to be used by a broker definition file.	<a href="#">89</a>
EXPORT_DELETE	Specification that the exported records from the UEC events database table are to be deleted upon –export EVENTS action	<a href="#">90</a>
FORMAT	Format of the output from the -export EVENTS action	<a href="#">91</a>
HELP	Write command option help.	<a href="#">92</a>
LIST	Specification to output the described broker definition in a user-friendly format.	<a href="#">93</a>
MESSAGE_LEVEL	Level of messages written.	<a href="#">94</a>
START_TIME	Start time of exported data	<a href="#">96</a>
UEC_PORT	TCP/IP port number of the UEC.	<a href="#">97</a>
USER_ID	UEC user ID or account with which brokers will be modified.	<a href="#">98</a>
USER_PASSWORD	Password associated with USER_ID.	<a href="#">99</a>
VERSION	Write program version.	<a href="#">100</a>

Table 3.1 UECLoad Configuration Options

## 3.4 ADD

### Description

---

The ADD option specifies that the action being taken is to add Broker definitions in the UEC database.

Valid actions are [ADD](#), [DELETE](#), [EXPORT](#), and [LIST](#). Only one action can be specified at any one time.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-add				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Values

---

(There are no values associated with ADD.)

## 3.5 ARCFILE

### Description

---

The ARCFILE option specifies the name of an archived file to retrieve for export.

Retrieval of archived data will export data directly into CSV or XML format.

Note: If ARCFILE is used, the [UEC\\_PORT](#), [USER\\_ID](#), and [USER\\_PASSWORD](#) options are ignored, since no connection is made to the UEC for this operation.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-arcfile <i>filename</i>				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Values

---

*filename* is the name of the file to retrieve.

## 3.6 BROKER\_DEFFILE

### Description

---

The BROKER\_DEFFILE option specifies the Broker definition file (**deffile**).

The **deffile** is used to specify multiple Broker definitions to be added or deleted to the UEC.

If used with the **EXPORT** option, the definition file is created with the results of the export action.

BROKER\_DEFFILE is not valid for use with the **LIST** option.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-deffile <i>filename</i>				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Values

---

*filename* is the name of the definition file.

## 3.7 BROKER\_DESCRIPTION

### Description

---

The BROKER\_DESCRIPTION option specifies a description of the Broker being added or deleted in the UEC database.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-broker_desc <i>description</i>				✓	✓
Environment Variable	UECLBROKERDESC= <i>description</i>				✓	✓
Definition File Keyword	broker_desc <i>description</i>				✓	✓

### Values

---

*description* is the description of the Broker being added or deleted.

Note: Since *description* can contain spaces, it should be enclosed in double ( " ) quotation marks.

## 3.8 BROKER\_HOST

### Description

---

The BROKER\_HOST option specifies the host network address of the Broker being added, deleted, or viewed in the UEC database.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-broker_host <i>address</i>				✓	✓
Environment Variable	UECLBROKER HOST= <i>address</i>				✓	✓
Definition File Keyword	broker_host <i>address</i>				✓	✓

### Values

---

*address* is the host network address of the Broker.

*address* can be specified in either of the following formats:

- Dotted format (1.2.3.4)
- Host domain name

If BROKER\_HOST is used with the [LIST](#) or [EXPORT](#) option, *address* can contain wildcards (for example, 1.2.3.\* or host1\*). In these examples, all broker host addresses that begin with 1.2.3 or host1, respectively, would be matched.

## 3.9 BROKER\_NAME

### Description

---

The BROKER\_NAME option specifies the unique name of a Broker being added, deleted, or viewed in the UEC database.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-broker_name <i>name</i>				✓	✓
Environment Variable	UECLBROKERNAME= <i>name</i>				✓	✓
Definition File Keyword	broker_name <i>name</i>				✓	✓

### Values

---

*name* is the name of the Broker.

If BROKER\_NAME is used with the [LIST](#) or [EXPORT](#) option, *name* can contain wildcards (for example, **broker\***). In this example, all broker names that begin with **broker1** would be matched.

## 3.10 BROKER\_PORT

### Description

---

The BROKER\_PORT option specifies the TCP/IP port of the Broker being added, deleted, or viewed in the UEC database.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-broker_port <i>port</i>				✓	✓
Environment Variable	UECLBROKERPORT= <i>port</i>					
Definition File Keyword	broker_port <i>port</i>					

### Values

---

*port* is the TCP/IP port of the Broker.

*port* can be specified in either of the following formats:

- Number (for example, 7887)
- Service name (for example, **ubroker**)

## 3.11 CODE\_PAGE

### Description

The CODE\_PAGE option specifies the character code page that is used to translate text data received and transmitted over the network.

The Universal Translate Table (UTT) files are used to translate between Unicode and the local single-byte code page.

### Usage

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	<code>-t codepage</code>				✓	✓
Command Line Option, Long Form	<code>-codepage codepage</code>				✓	✓
Environment Variable	<code>UECLDCODEPAGE=codepage</code>				✓	✓
Definition File Keyword	n/a					

### Value

*codepage* is the character code page that is used to translate data.

*codepage* references a Universal Translate Table (UTT) file provided with the product (see Section 4.3 UTT Files for information on UTT files). UTT files are used to translate between Unicode and the local single-byte code page. (All UTT files end with an extension of `.utt`.)

#### [Default

**The default code page is different for different operating systems:**

- ISO8859-1 (8-bit ASCII) ASCII-based operating systems
- IBM1047 (EBCDIC) EBCDIC-based operating system]

See Section 4.2 Character Code Pages for a complete list of character code pages provided by Stonebranch Inc. for use with Universal Products.

## 3.12 COMMAND\_FILE\_ENCRYPTED

### Description

---

The COMMAND\_FILE\_ENCRYPTED option specifies the ddname / file name of a data set / file containing encrypted values for command line option parameters.

Command files specify an additional source of command line options. Storing options in a file can be used in situations where it is not desirable to explicitly specify them on the command line. The options read from the file are processed exactly like options specified on the command line. The options must be in their respective command line formats.

UECLoad can process command files that are either encrypted or in plain text (see the [COMMAND\\_FILE\\_PLAIN](#) option). Encrypted command files are an excellent place to store sensitive data such as user IDs and passwords. Command files (encrypted or not) that contain sensitive data should be protected from unauthorized read access with a security system, such as RACF.

Use the Universal Encrypt utility provided with Universal Command to encrypt a plain text command file. (For information on Universal Encrypt, see the Universal Products Utilities 3.2.0 User Guide). If a key was used to encrypt the file, the same key must be supplied using the [ENCRYPTION\\_KEY](#) option.

Note: If a data set / file is specified in this option, it should not be specified additionally in the [COMMAND\\_FILE\\_PLAIN](#) option. If it is, the data set / file specified in [COMMAND\\_FILE\\_PLAIN](#) will be used.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	<code>-x ddname or filename</code>				✓	✓
Command Line Option, Long Form	<code>-encryptedfile ddname or filename</code>				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Value

---

*filename* is the name of the file containing the encrypted command parameter values.

## 3.13 COMMAND\_FILE\_PLAIN

### Description

---

The COMMAND\_FILE\_PLAIN option specifies the ddname / file name of a data set / file containing plain text values for command line option parameters.

Command files specify an additional source of command line options. Storing options in a file can be used in situations where it is not desirable to explicitly specify them on the command line. The options read from the file are processed exactly like options specified on the command line. The options must be in their respective command line formats.

UECLoad can process command files that are either in plain text or encrypted (see the [COMMAND\\_FILE\\_ENCRYPTED](#) option). It is strongly recommended that plain text files be further protected from unauthorized access using a native operating system security method, such as RACF.

Note: If a data set / file is specified in this option, it should not be specified additionally in the [COMMAND\\_FILE\\_ENCRYPTED](#) option. If it is, the data set / file specified in COMMAND\_FILE\_PLAIN will be used.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	<code>-f ddname or filename</code>				✓	✓
Command Line Option, Long Form	<code>-file ddname or filename</code>				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Value

---

*filename* is the ddname / file name of the data set / file containing the parameters and their values.

## 3.14 DELETE

### Description

---

The DELETE option specifies that the action being taken is the deletion of Broker definitions in the UEC database.

Valid actions are [ADD](#), [DELETE](#), [EXPORT](#), and [LIST](#). Only one action can be specified at any one time.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-delete				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Values

---

(There are no values associated with DELETE.)

## 3.15 ENCRYPTION\_KEY

### Description

---

The ENCRYPTION\_KEY option specifies the key used to encrypt the command file specified by the [COMMAND\\_FILE\\_ENCRYPTED](#) option.

This key acts much like a password for the encrypted command file in that it can be used to protect the file from decryption by unauthorized users.

If a key was used to encrypt a command file (when Universal Encrypt was run), that same key must be specified to decrypt the file, or the decryption will fail. If no key is specified, the default key is used.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	-K key				✓	✓
Command Line Option, Long Form	-key key				✓	✓
Environment Variable	UCMDKEY=key					
Definition File Keyword	n/a					

### Value

---

*key* is the key used to encrypt the command file.

## 3.16 END\_TIME

### Description

---

The END\_TIME option specifies the ending date and time selection criteria of the export of the UEC events database table.

Note: END\_TIME is required when the –export EVENTS action is used (see Section [3.17 EXPORT](#)).

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	-e <i>enddate[,endtime]</i>				✓	✓
Command Line Option, Long Form	-etime <i>enddate[,endtime]</i>				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Value

---

*enddate* must be specified in the following format: YYYY/MM/DD

*endtime* must be specified in the following format: HH:MM:SS

Upon export, event records can be selected by using an asterisk ( \* ) for the *enddate*.

A rolling date can be specified with an asterisk ( \* ) followed by a negative value (for example, \* -2 selects records that were generated prior to two days before the current date). If *endtime* is not specified, a value of 23:59:59 is used.

## 3.17 EXPORT

### Description

---

The EXPORT option specifies that the action being taken is the export of a UEC database. By default, EXPORT outputs the UEC broker definitions in a format that can be used at a later time as a broker definition file.

Note: Valid actions are [ADD](#), [DELETE](#), [EXPORT](#), and [LIST](#). Only one action can be specified at any one time.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-export [ <i>EVENTS</i> ]				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Values

---

*EVENTS* specifies that the events database table from UEC is exported.

The format of the output is either [XML](#), [CSV](#), or [ARC](#) (specified via the [FORMAT](#) option). If the format is not specified, [XML](#) is used by default.

## 3.18 EXPORT\_DELETE

### Description

---

The EXPORT\_DELETE option specifies that the exported records from the UEC events database table are to be deleted upon `-export EVENTS` action (see Section 3.17 EXPORT).

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	<code>-export_delete</code>				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Values

---

(There are no values for EXPORT\_DELETE.)

## 3.19 FORMAT

### Description

The FORMAT option specifies the format of the output from the **-export EVENTS** action.

### Usage

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	<code>-format format</code>				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Values

*format* is the format of the output from **-export EVENTS**.

*format* can be either:

- **XML** Event data is exported as an XML (extensible markup language) document. XML is often used for exchanging data between two systems.
- **CSV** Event data is exported as a CSV (comma separated value) text file. The CSV file can be used by most spreadsheet software, such as Microsoft Excel.
- **ARC** Event data is exported in ARC (archival) format for long-term storage. The exported ARC format data (written in UTF-8) is portable between operating systems with differing code pages.

The purpose of exporting data in the **ARC** format is to back up all UES data. The user must have permission to all Universal Brokers in order to export data for all UES records. This is best accomplished via the Universal Management Console application by assigning the **All Agents** group to the user that is performing the UES export archive. (See Section [3.5.2 Assigning Agent Groups to a User](#) in the Universal Enterprise Controller Client Applications User Guide.)

**[Default is XML.]**

## 3.20 HELP

### Description

---

The HELP option displays a description of the command options and their format.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	-h				✓	✓
Command Line Option, Long Form	-help				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Value

---

(There are no values for the HELP option.)

## 3.21 LIST

### Description

---

The LIST option specifies that the action being taken is to output current UEC Broker definitions in a user-friendly format.

Valid actions are [ADD](#), [DELETE](#), [EXPORT](#), and [LIST](#). Only one action can be specified at any one time.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	n/a					
Command Line Option, Long Form	-list				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Values

---

(There are no values associated with LIST.)

## 3.22 MESSAGE\_LEVEL

### Description

---

The MESSAGE\_LEVEL option specifies the level of messages to write.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	-l /level/				✓	✓
Command Line Option, Long Form	-level /level/				✓	✓
Environment Variable	UECLLEVEL=/level/				✓	✓
Definition File Keyword	n/a					

### Values

---

/level/ indicates either of the following level of messages:

- **trace**  
Writes trace messages used for diagnostic purposes (see [Trace Files](#), below).  
Note: Use **trace** only as directed by Stonebranch, Inc. [Customer Support](#).
- **audit**  
Writes audit, informational, warning, and error messages.
- **info**  
Writes informational, warning, and error messages.
- **warn**  
Writes warning and error messages.
- **error**  
Writes error messages only.

**[Default is info.]**

## Trace Files

---

### Windows

Trace file name is **uecload.trc**. It is created in the working directory of the user who executed **uecload**.

### z/OS

Trace file is written to the data set referenced by the **UNVTRACE** ddname.

## 3.23 START\_TIME

### Description

---

The START\_TIME option specifies the starting date and time selection criteria of the export of the UEC events database table.

Note: START\_TIME is required when the –export EVENTS action is used (see Section [3.17 EXPORT](#)).

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	<code>-s startdate[,starttime]</code>				✓	✓
Command Line Option, Long Form	<code>-stime startdate[,starttime]</code>				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Value

---

*startdate* must be specified in the following format: YYYY/MM/DD

*starttime* must be specified in the following format: HH:MM:SS

Upon export, event records can be selected by using an asterisk ( \* ) for the *startdate*.

A rolling date can be specified with an asterisk ( \* ) followed by a negative value (for example, \* -2 selects records that were generated prior to two days before the current date). If *starttime* is not specified, a value of 00:00:00 is used.

## 3.24 UEC\_PORT

### Description

---

The UEC\_PORT option specifies the TCP port on which to send the command.

The UEC must be running and accepting connections on the specified port.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	<code>-p <i>port</i></code>				✓	✓
Command Line Option, Long Form	<code>-port <i>port</i></code>				✓	✓
Environment Variable	<code>UECLPORT=<i>port</i></code>				✓	✓
Definition File Keyword	n/a					

### Values

---

*port* is the TCP/IP port on which to send the command.

*port* can be specified in either of the following formats:

- Number (for example, **8778**)
- Service name (for example, **ueclload**)

**[Default is 8778.]**

## 3.25 USER\_ID

### Description

---

The USER\_ID option specifies the user identifier that is used to sign on to the UEC.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	-u <i>user</i>				✓	✓
Command Line Option, Long Form	-userid <i>user</i>				✓	✓
Environment Variable	UECLUSERID= <i>user</i>				✓	✓
Definition File Keyword	n/a					

### Values

---

*user* is the user identifier that is used to sign on to the remote computer.

Note: *user* must be a valid user identifier in the UEC database.

## 3.26 USER\_PASSWORD

### Description

---

The USER\_PASSWORD option specifies the password for the user identifier that is specified in the [USER\\_ID](#) option.

The password always is encrypted.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	<code>-w password</code>				✓	✓
Command Line Option, Long Form	<code>-pwd password</code>				✓	✓
Environment Variable	<code>UECLPWD=password</code>				✓	
Definition File Keyword	n/a					

### Values

---

*password* is the password for the user identifier.

*password* must be a valid password for the user identifier in the UEC database.

## 3.27 VERSION

### Description

---

The VERSION option writes the program version information and copyright.

### Usage

---

Method	Syntax	OS/400	NonStop	UNIX	Windows	z/OS
Command Line Option, Short Form	-v				✓	✓
Command Line Option, Long Form	-version				✓	✓
Environment Variable	n/a					
Definition File Keyword	n/a					

### Values

---

(There are no values to be specified for this option.)

---

# Chapter 4

## Additional Information

---

### 4.1 Overview

This chapter provides additional information related to Universal Enterprise Controller.

[Table 4.1](#), below, identifies this information and provides a link to its location in this document.

Information	Description	Page
Character Code Pages	Character Code pages for use with Universal Enterprise Controller.	<a href="#">102</a>
UTT Files	Universal Translate Table (UTT) files are used to translate between Unicode and the local single-byte code page.	<a href="#">104</a>

Table 4.1 Universal Enterprise Controller - Additional Information

## 4.2 Character Code Pages

[Table 4.2](#) identifies the character code pages provided by Stonebranch Inc. for use with Universal Products on each supported operating system.

Code Page	CCSID	z/OS	UNIX	Windows	OS/400		HP NonStop
					HFS	LIB	
IBM037	037	✓			✓	✓	
IBM273	273	✓			✓	✓	
IBM277	277	✓			✓	✓	
IBM278	278	✓			✓	✓	
IBM280	280	✓			✓	✓	
IBM284	284	✓			✓	✓	
IBM500	500	✓			✓	✓	
IBM875	875	✓					
IBM1047							
IBM1140	1140	✓			✓	✓	
IBM1141	1141	✓			✓	✓	
IBM1142	1142	✓			✓	✓	
IBM1143	1143	✓			✓	✓	
IBM1144	1144	✓			✓	✓	
IBM1145	1145	✓			✓	✓	
IBM1146	1146	✓			✓	✓	
IBM1147	1147	✓			✓	✓	
IBM1148	1148	✓			✓	✓	
IBM4971	4971	✓					
ISO8859-1	819		✓	✓	✓		✓
ISO8859-2	912		✓	✓	✓		✓
ISO8859-3	913		✓	✓	✓		✓
ISO8859-4	914		✓	✓	✓		✓
ISO8859-5	915		✓	✓	✓		✓
ISO8859-6	1089		✓	✓	✓		✓
ISO8859-7	813		✓	✓	✓		✓
ISO8859-8	916		✓	✓	✓		✓
ISO8859-9	920		✓	✓	✓		✓
ISO8859-10			✓	✓	✓		✓
ISO8859-13	921		✓	✓	✓		✓
ISO8859-14			✓	✓	✓		✓
ISO8859-15	923		✓	✓	✓		✓
PC437	437			✓	✓		

Code Page	CCSID	z/OS	UNIX	Windows	OS/400		HP NonStop
					HFS	LIB	
PC737	737			✓	✓		
PC775	775			✓	✓		
PC850	850			✓	✓		
PC852	852			✓	✓		
PC855	855			✓	✓		
PC857	857			✓	✓		
PC860	860			✓	✓		
PC861	861			✓	✓		
PC862	862			✓	✓		
PC863	863			✓	✓		
PC864	864			✓	✓		
PC865	865			✓	✓		
PC866	866			✓	✓		
PC869	869			✓	✓		
PC874	874			✓	✓		
WIN1250	1250			✓	✓		
WIN1251	1251			✓	✓		
WIN1252	1252			✓	✓		
WIN1253	1253			✓	✓		
WIN1254	1254			✓	✓		
WIN1255	1255			✓	✓		
WIN1256	1256			✓	✓		
WIN1257	1257			✓	✓		
WIN1258	1258			✓	✓		

Table 4.2 Character Code Pages

## 4.3 UTT Files

Universal Translate Table (UTT) files are used to translate between Unicode and the local single-byte code page.

Operating System	UTT File Location
z/OS	UTT files are members of the PDS allocated to the Broker ddname <b>UNVNLS</b> . <i>codepage</i> specifies the member name.
Windows	UTT files are located in the <b>NLS</b> subdirectory of the installation directory. <i>codepage</i> is the base file name of the UTT file.

Table 4.3 UTT File Locations

---

# Appendix A

## Customer Support

---

Stonebranch, Inc. provides customer support, via telephone and e-mail, for Universal Enterprise Controller and all Universal Products.

### TELEPHONE

---

Customer support via telephone is available 24 hours per day, 7 days per week.

**North America**

**(+1) 678 366-7887, extension 6**

**(+1) 877 366-7887, extension 6 [toll-free]**

**Europe**

**+49 (0) 700 5566 7887**

### E-MAIL

---

**All Locations**

**[support@stonebranch.com](mailto:support@stonebranch.com)**

Customer support contact via e-mail also can be made via the Stonebranch website:

**[www.stonebranch.com](http://www.stonebranch.com)**





**950 North Point Parkway, Suite 200**

**Alpharetta, Georgia 30005**

**U.S.A.**

